

## Segment T-Stück 90° reduziert aus PE-HD / PE 100

für Stumpf- und Muffenschweißung  
 Unverstärkt aus Rohr geschweißt  
 (Verschwächungsbeiwert = 0,6)

D1 mm	D2 mm	z mm	L mm	SDR 17/17,6 Gewicht in kg	SDR 11 Gewicht in kg	andere SDR Abmessungen auf Anfrage
90	50	195	450	0,75	1,08	
90	63	195	465	0,80	1,18	
110	50	205	450	1,06	1,54	
110	63	205	465	1,15	1,67	
110	75	205	475	1,24	1,80	
125	63	215	465	1,09	2,51	
125	75	215	475	1,54	2,16	
125	90	215	490	1,58	2,22	
140	63	220	465	1,84	2,67	
140	75	220	475	1,93	2,82	
140	90	220	490	2,07	3,03	
140	110	220	510	2,43	3,37	
160	63	230	465	2,27	3,34	
160	75	230	475	2,37	3,51	
160	90	230	490	2,44	3,74	
160	110	230	510	2,79	4,12	
160	125	230	525	3,00	4,43	
180	63	240	465	2,83	4,11	
180	75	240	475	2,96	4,36	
180	90	240	490	3,14	4,62	
180	110	240	510	3,43	5,04	
180	125	240	525	3,51	5,17	
180	140	240	540	3,94	5,80	
200	63	250	465	3,57	5,30	
200	75	250	475	3,75	5,50	
200	90	250	490	3,95	5,82	
200	110	250	510	4,26	6,28	
200	125	250	525	4,52	6,69	
200	140	250	540	4,74	7,14	
200	160	250	560	5,22	7,70	

## Segment T-Stück 90° reduziert aus PE-HD / PE 100

für Stumpf- und Muffenschweißung  
 Unverstärkt aus Rohr geschweißt  
 (Verschwächungsbeiwert = 0,6)

D1 mm	D2 mm	z mm	L mm	SDR 17/17,6 Gewicht in kg	SDR 11 Gewicht in kg	andere SDR Abmessungen auf Anfrage
225	63	265	465	4,35	6,50	
225	75	265	475	4,50	6,80	
225	90	265	490	4,80	7,14	
225	110	265	510	5,10	7,70	
225	125	265	525	5,40	8,13	
225	140	265	540	5,80	8,64	
225	160	265	560	6,19	9,30	
225	180	265	580	7,03	10,00	
250	75	275	475	5,50	8,10	
250	90	275	490	5,76	8,50	
250	110	275	510	6,17	9,10	
250	125	275	525	6,50	9,60	
250	140	275	540	6,89	10,15	
250	160	275	560	7,37	10,90	
250	180	275	580	7,92	11,70	
250	200	275	600	8,58	12,60	
280	90	290	490	6,91	10,50	
280	110	290	510	7,40	11,30	
280	125	290	525	7,75	11,80	
280	140	290	540	8,20	12,50	
280	160	290	560	9,00	13,30	
280	180	290	580	9,62	14,20	
280	200	290	600	10,50	15,30	
280	225	290	625	11,15	16,55	
315	90	360	500	9,30	13,40	
315	110	360	510	9,65	14,20	
315	125	360	530	10,20	15,10	
315	140	360	545	10,80	15,90	
315	160	360	565	11,55	16,90	
315	180	360	585	12,20	18,00	
315	200	360	600	13,10	19,30	
315	225	360	630	13,70	20,90	
315	250	360	650	15,30	22,50	

## Segment T-Stück 90° reduziert aus PE-HD / PE 100

für Stumpf- und Muffenschweißung  
 Unverstärkt aus Rohr geschweißt  
 (Verschwächungsbeiwert = 0,6)

D1 mm	D2 mm	z mm	L mm	SDR 17/17,6 Gewicht in kg	SDR 11 Gewicht in kg	andere SDR Abmessungen auf Anfrage
355	110	380	610	14,30	21,00	
355	125	380	630	15,00	22,00	
355	140	380	640	15,50	22,80	
355	160	380	660	16,30	24,00	
355	180	380	680	17,20	25,30	
355	200	380	700	18,30	26,80	
355	225	380	730	19,60	30,90	
355	250	380	750	20,80	33,80	
400	110	400	610	17,90	26,50	
400	125	400	630	18,70	27,60	
400	140	400	640	19,30	28,60	
400	160	400	660	20,30	30,00	
400	180	400	680	21,30	31,50	
400	200	400	700	22,50	33,30	
400	225	400	730	24,00	35,50	
400	250	400	750	25,40	41,60	
400	280	400	780	27,30	44,50	
400	315	400	820	29,90	48,30	
450	110	425	610	22,60	32,60	
450	125	425	630	23,50	34,00	
450	140	425	640	24,30	35,00	
450	160	425	660	25,80	36,70	
450	180	425	680	26,60	38,40	
450	200	425	700	27,90	40,50	
450	225	425	730	29,70	48,20	
450	250	425	750	31,30	50,50	
450	280	425	780	33,50	53,70	
450	315	425	820	36,50	58,10	
450	355	425	860	39,90	63,10	
500	110	450	610	27,80	40,80	
500	125	450	630	28,90	42,50	
500	140	450	640	29,70	43,70	

## Segment T-Stück 90° reduziert aus PE-HD / PE 100

für Stumpf- und Muffenschweißung  
 Unverstärkt aus Rohr geschweißt  
 (Verschwächungsbeiwert = 0,6)

D1 mm	D2 mm	z mm	L mm	SDR 17/17,6 Gewicht in kg	SDR 11 Gewicht in kg	andere SDR Abmessungen auf Anfrage
500	160	450	660	31,00	45,60	
500	180	450	680	32,40	47,70	
500	200	450	700	34,00	50,10	
500	225	450	730	36,00	53,10	
500	250	450	750	37,90	62,80	
500	280	450	780	40,40	65,90	
500	315	450	820	43,80	70,90	
500	355	450	860	47,70	76,60	
500	400	450	900	52,10	83,20	
560	110	580	610	34,80	51,20	
560	125	580	630	36,20	53,40	
560	140	580	640	37,30	54,90	
560	160	580	660	38,90	57,00	
560	180	580	680	40,70	59,90	
560	200	580	700	42,60	62,70	
560	225	580	730	45,30	66,70	
560	250	580	750	47,60	76,50	
560	280	580	780	50,90	83,00	
560	315	580	820	55,20	89,40	
560	355	580	860	60,20	96,60	
560	400	580	900	65,70	105,00	
630	110	615	610	43,80	64,80	
630	125	615	630	45,50	67,40	
630	140	615	640	46,70	69,10	
630	160	615	660	48,70	72,10	
630	180	615	680	50,80	75,20	
630	200	615	700	53,10	78,50	
630	225	615	730	56,30	83,30	
630	250	615	750	58,90	97,50	
630	280	615	780	62,80	102,90	
630	315	615	820	67,80	110,50	
630	355	615	900	76,30	123,00	
630	400	615	900	79,90	128,50	

## Segment T-Stück 90° reduziert aus PE-HD / PE 100

für Stumpf- und Muffenschweißung  
 Unverstärkt aus Rohr geschweißt  
 (Verschwächungsbeiwert = 0,6)

D1 mm	D2 mm	z mm	L mm	SDR 17/17,6 Gewicht in kg	SDR 11 Gewicht in kg	andere SDR Abmessungen auf Anfrage
630	450	615	950	87,90	139,70	
710	160	655	660	60,10	88,00	
710	180	655	680	62,20	91,10	
710	200	655	700	64,40	94,20	
710	225	655	730	67,60	98,90	
710	250	655	850	78,90	115,40	
710	280	655	880	82,40	120,60	
710	315	655	920	87,10	127,40	
710	355	655	1000	96,00	139,80	
710	400	655	1000	98,40	142,50	
710	450	655	1050	104,30	151,30	
800	160	700	660	75,80	108,00	
800	180	700	680	78,30	111,70	
800	200	700	700	81,00	115,60	
800	225	700	730	85,20	121,20	
800	250	700	850	99,10	141,80	
800	280	700	880	103,40	147,40	
800	315	700	920	108,90	155,30	
800	355	700	1000	119,40	170,30	
800	400	700	1000	121,20	172,50	
800	450	700	1050	129,10	184,60	
800	500	700	1100	137,30	196,50	
900	160	750	660	95,40	135,10	
900	180	750	680	98,60	140,30	
900	200	750	700	101,90	144,90	
900	225	750	730	106,70	151,80	
900	250	750	850	124,40	176,90	
900	280	750	880	129,60	184,40	
900	315	750	920	136,40	194,10	
900	355	750	1000	149,20	211,80	
900	400	750	1000	151,00	224,50	
900	450	750	1050	160,30	228,40	
900	500	750	1100	169,80	242,70	
900	560	750	1200	187,60	267,50	