

## Segment T-Stück 90° aus PE-HD / PE 100

für Stumpf- und Muffenschweißung  
 Unverstärkt aus Rohr geschweißt  
 (Verschwächungsbeiwert = 0,6)

DA	L	z	L1	SDR 17/17,6 Gewicht in kg	SDR 11 Gewicht in kg	andere SDR Abmessungen auf Anfrage
140 mm	440	220	150	2,10	3,00	
160 mm	460	230	150	2,80	4,20	
180 mm	480	240	150	3,70	5,40	
200 mm	500	250	150	4,70	6,90	
225 mm	530	265	150	6,20	9,10	
250 mm	750	375	250	11,00	16,20	
280 mm	780	390	250	14,40	21,40	
315 mm	920	460	300	21,70	32,00	
355 mm	960	480	300	28,30	41,60	
400 mm	1000	500	300	37,80	55,70	
450 mm	1050	525	300	48,50	71,70	
500 mm	1200	600	350	68,80	101,30	
560 mm	1260	630	350	89,30	131,70	
630 mm	1330	665	350	118,00	173,40	
710 mm	1410	705	350	158,90	234,00	
800 mm	1500	750	350	209,50	296,00	
900 mm	1700	850	400	305,30	425,30	
1000 mm	1800	900	400	394,00		
1200 mm	2200	1050	450	639,00		

